

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



DIELECTRIC STRENGTH TESTER MODEL AVC-25V

IINPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 95 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 95 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



DIELECTRIC STRENGTH TESTER MODEL AV-25V-5

IINPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



DIELECTRIC STRENGTH TESTER MODEL AV-25V-10

IINPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-5**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-5 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 5 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-5V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 5 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-5 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 3-5 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-10**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-10 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 10 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-10V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 10 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: \pm 2% of full scale
AMMETER	0-10 mA ac Accuracy: \pm 2% of full scale
TRIP CURRENT	Adjustable 3-10 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-20V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 20 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-20 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 3-20 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-30V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 30 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-30 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 3-30 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-40V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 40 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: \pm 2% of full scale
AMMETER	0-40 mA ac Accuracy: \pm 2% of full scale
TRIP CURRENT	Adjustable 3-40 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



DIELECTRIC STRENGTH TESTER MODEL AVC-25VA

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 95 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-100 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 95 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	28W x 16D x 16H cm (11W x 6.5D x 6.5H inches)
WEIGHT	9 kg (20 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AVC-25V-SD**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 95 mA
TRANSFORMER	Rated 500 VA Short duty cycle
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-100 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Fixed @ 95 mA $\pm 5\%$
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off switch, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W clips. Each is 2 meters (6 ft) long.
SIZE	23W x 15D x 20H cm (9W x 6D x 8H inches)
WEIGHT	5.5 kg (12 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, electrical-motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-25VA-200V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-2500 V ac @ 200 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-2500 V ac Accuracy: $\pm 2\%$ of full scale
AMMETER	0-250 mA ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 50-200 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off circuit-breaker, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	36W x 24D x 18H cm (14W x 9.5D x 7H inches)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, electrical-motors, home-appliances and other electrical products.



**DIELECTRIC STRENGTH TESTER
MODEL AV-30VA-150V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-3000 V ac @ 150 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-3000 V ac Accuracy: \pm 2% of full scale
AMMETER	0-150 mA ac Accuracy: \pm 2% of full scale
TRIP CURRENT	Adjustable 50-150 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off circuit-breaker, one fuse, one reset push-button, one high-voltage adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	36W x 24D x 18H cm (14W x 9.5D x 7H inches)
WEIGHT	14 kg (31 lb)