



Que-2-TXT™
 Questions?
 scan to text us fast



HID EQUAL LED LAMPS

240° BEAM ANGLE



specifications

Consumption	Voltage	CRI	Lens	Heat Sink	L70 hours	Surge Protection	Ambient Temp (F)	Power Factor	UL listing	THD	Beam Angle	Enclosed Fixture Rated
27W	120 - 277 V ⚡	> 80	frosted polycarbonate	plastic-coated aluminum	50,000	2.5 KV built-in	-22° - 113°	> 0.9	wet location	< 20%	240°	yes

select your lamp

Part Number	Color Temp	Base	Lumen Output	Efficacy
GI-CC-240WW100-UL3	2700K	E26	3500	129.6 lm / W
GI-CC-240C100-UL3	5000K	E26	3500	129.6 lm / W

other

Dimensions	Warranty	Weight	Case QTY
3.93" (D) x 7.08" (L)	6 years	1.03 lbs	12 pcs



Features

- > 100% potted drivers- protects electronics against moisture and vibration
- > 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations
- > Shatterproof
- > Waterproof design for weather-exposed applications
- > Frosted lens design for open fixtures

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.



/greenignite
 @greenignite



www.greenignite.com



info@greenignite.com



1-877-560-3779