




VMDTC100-75-M16-40-Z

Ruland VMDTC100-75-M16-40-Z, Vibration Isolation Mount, 100mm OD, M16 Tapped Holes, 16mm Tapped Hole Depths, 75mm Height, 40 Shore A Natural Rubber Jacket, Steel



Description

Ruland VMDTC100-75-M16-40-Z is a vibration isolation mount with two tapped holes. It has a 100mm outside diameter, M16 tapped holes, 16mm tapped hole depths, and 75mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. VMDTC100-75-M16-40-Z can be mounted to the system by threading it onto an existing stud on the components. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 40 Shore A hardness for high dampening and shock absorption. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMDTC100-75-M16-40-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	3.94 in (100 mm)	Height (H1)	2.95 in (75 mm)
Thread (TH)	M16 x 2.0	Plate Thickness (PT)	0.12 in (3 mm)
Tapped Hole Depth (LT)	0.63 in (16.1 mm)	Spring Rate	2369.71 lb/in (415 N/mm)
Shore Hardness	40A (+/- 5)	Max Deflection	0.74 in (18.8 mm)
Max Axial Load	1751.26 lb (7790 N)	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Zinc Plated Steel
Metallic Body Finish	Zinc-Plated	Manufacturer	JW Winco/ Otto Ganter
Country of Origin	Hungary	Weight (lbs)	2.057100
UPC	634529355039	Tariff Code	4016.99.6000
UNSPC	31162804		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		