

**Product Specifications**

**Part Numbers Information**

**Electrical Specifications**

600VAC – 1A - 30A  
300VDC – 1A - 30A

**Standards**

1A-30A - UL Listed to Standard 248-4. File E523284  
1A-30A - CSA Certified Standard C22.2 No. 248.4. File E523284




Branch-circuit Fuses

**Interrupting Rating**


200,000 amperes at 600V AC(1A-30A)  
20,000 amperes at 300V DC(1A-30A)

**Mechanical Dimensions: Inches [mm]**



Optifuse P/N	Current Rating
FPK-R-1A	1A
FPK-R-1.25A	1.25A
FPK-R-1.5A	1.5A
FPK-R-1.6A	1.6A
FPK-R-2A	2A
FPK-R-2.5A	2.5A
FPK-R-3A	3A
FPK-R-3.15A	3.15A
FPK-R-3.5A	3.5A
FPK-R-4A	4A
FPK-R-5A	5A
FPK-R-6A	6A
FPK-R-6.3A	6.3A
FPK-R-7A	7A
FPK-R-8A	8A
FPK-R-9A	9A
FPK-R-10A	10A
FPK-R-12A	12A
FPK-R-15A	15A
FPK-R-16A	16A
FPK-R-20A	20A
FPK-R-25A	25A
FPK-R-30A	30A

**Time vs. Percent of Rated Current**



% of Rated Current	Blowing Time
100%	15 minuts Min.
153%	1 hr Max.
200%	4 minuts Max.

**Class CC Midget Fuse - Fast Acting**  
**13/32" x 1 1/2"**

**FPK-R**



**Rev Date of issue Revision Notes**

**Designed Approved**

A	01-02-2022	Initial Drawing	RC	OF
---	------------	-----------------	----	----