

WIDTH 20.6 Max.

Electrical Rating


- AC (Resistive) : 15A at 125V, 15A at 250V.
- AC (Inductive) : 5A at 125V, 5A at 250V.
- DC (Resistive) : 0.5A at 125V, 0.25A at 250V.
- DC (Inductive) : 0.03A at 125V, 0.02A at 250V.
- Insulation resistance : 1000 Megaohms
- Contact resistance (Max.) : 10 miliohms.
- Voltage proof : 1 KV AC for 1 minute.
- Free position (Max.) : 40.8mm
- Operating position : 39.3±0.33mm
- Movement Differential (Max.) : 0.08mm
- Available Overtravel : 4.6mm
- Actuating Force (Max.) : 723 gms.
- Release Force(Min.) : 170 gms.
- Actuator : Spring plunger actuator with rubber cowl protection.
- Mechanism : Single-pole, changeover.
- Terminals : Three M3 screws with washers
beneath insulated cover.
- Housing : Zinc alloy die cast

RoHS COMPLIANT

CAT. NO. : MBC-1

ISS.	DATE	MODIFICATION	SIGN.

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.1	MICRO SWITCH SERIES 'B'		DIMENSIONS IN MM	
				DATE
			DESIGN	19.03.11
			DRAWN	19.03.11
			CHKD.	
			APPD.	
			DRG. NO.	
			MBCU-103.	A4.
			SHEET	1 OF 1



ESSEN DEINKI,
22, INDUSTRIAL AREA, PHASE II,
CHANDIGARH - 160 002.

C9\productscan\electrical\customer drgs std switch\B Series